

## Forklift Seat Belt

Forklift Seat Belts - This guideline purpose is to be able to explain the Regulation necessities for the utilization of operator seatbelts or restraints on lift trucks. It is the employers' accountability to be able to make certain that each machinery, piece of equipment and device inside the workplace is selected and utilized correctly and worked in accordance with the manufacturer's directions.

Regarding their inspection, fabrication, use, design and maintenance Rough Terrain forklifts ought to meet the guidelines of ANSI Standard ASME B56.6-1992.

Side boom tractors and mobile machinery together with a Rollover Protective Structure, or ROPS for short, should contain seat belts which satisfy the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whichever mobile equipment includes seat belts required by law, the driver and subsequent passengers need to ensure they use the belts every time the vehicle is in motion or engaged in operation as this could cause the machinery to become unbalanced and thus, not safe.

If a seat belt or various operator restraint is needed on a forklift.

The seat belt requirements while working a forklift depend on various factors. Whether the forklift is equipped with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was made all add to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to powered industrial lift trucks, ANSI Standard ASME B56.1-1993 refers to an operator restraint device, enclosure or system. A driver restraint device, system, or enclosure is intended to help the driver in lessening the risk of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The system or restraint device can comprise a seat belt, although a seat belt is not necessarily a part of such equipment or system.